

Model: M08X/M08Y/M08Z

Description: Mid-distance Series of Card Reader

Features:

▶ Read indication, LED display, buzzer, digital signals management

▶ Protections function for output, water proof and damp proof design, suitable for outside environment

Glass discharge tube and semiconductor discharge circuit for output

RS485 output adopting multilevel thunder protection, bearing 15KV static strike

Excellent material for all products with strict examination, good consistency

Protected circuit for power to avoid damage by man-made operating error

Card reader specification:

Model	M08X	M08Y	M08Z
Size	230 X 230 X 35(mm)	230 X 230 X 35(mm)	230 X 230 X 35(mm)
Color	Dark Grev	Dark Grev	Dark Grev
Voltage	DC 12V	DC 12V	DC 12V
Current	≤100mA	≤100mA	≤100mA
Temperature	-10℃ -70℃	-10℃ - 70℃	-10℃ -70℃
Reading Range	70-100CM	70-100CM	70-100CM
Output Format	Wiegand 26/34, RS485/232	Wiegand 26/34, RS485/232	Wiegand 26/34, RS485/232
Card Type	EM-ID Mid-distance Card	EM-ID Mid-distance Card	EM-ID Mid-distance Card
Communication	≥100M	≥100M	≥100M