

Model: EL-500(LED)

Description: Single Door Magnetic Lock with LED (1200Lbs)

Parameters:

- ►Lock Size: 265Lx71.8Wx38.8H(mm)
- ►Armature plate: 185Lx60Wx13H(mm)
- ► Holding Force: 500kg(1200Lbs)
- ►Voltage: 12/24VDC+10%; Current Draw: 12V/420mA 24V/210mA
- ► Optional Bracket: EL-500L EL-500ZL
- Signal Output: Dry Contact, Max Rating of Contact Current 3A
- ►LED red indicates the door is unlock, Green indicates the door is lock
- Suitable for: Wooden door , Glass door , Metal door , Fireproof door
- Surface Temp: $\leq +20^{\circ}$ C; Operating Temp: $10 \sim +55^{\circ}$ C(14-131F)
- ► Suitable Humidity: 0~90% (non-condensing)
- ▶ Finishes for Shell: Anodized aluminum
- ▶ Finishes for Magnetic: Zinc
- ▶ Finishes for Armature: Zinc
- ►Weight: 4.5kg; Standard Packing: 4pcs

Features:

- Collinear Load Test 500kg,1200pounds
- ►Dual Voltage 12 or 24 VDC(optional)
- ► The Standard Voltage is 12VDC when Finished
- ► MOV Provides Reverse Current Protection
- Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- ►LED Indicates the Door Status
- ►Lock Status sensor(NO/NC/COM)
- ►Anti-Residual Magnetism Designed
- ► High Strength Material, Anodized Aluminum Housing
- Design with no Mechanical Failure
- ► Increase the holding Force, Dual Insulative Housing
- ►CE Certificate by European Union





EL-500ZL