

Fail Secure Electric Bolt W/Cylinder





Model: EL-600C(LED)/ EL-630C(LED)


Parameters

Lock Body	260Lx30Wx48H(mm)[YB-600C(LED)] 260Lx30Wx73H(mm)[YB-630C(LED)]
Magnetic Plate	100Lx25Wx2.5H(mm)
Bolt	16(prolongation)*16(diameter)(mm)
Signal Output	Lock signal NO/NC/COM(need order door signal)
Voltage	12VDC(24VDC can be customized)
Current	1200mA
Feature	Fail Secure
LED	Light on indicates unlocked, light off indicates locked
Suitable for	Wooden door, metal door, fireproof door, glass door
Material	304 stainless steel, wire draw finishing
Weight	1.6kg/1.8kg


Dimensions




EL-600C(LED)



EL-600C(LED)






EL-630C(LED)





EL-630C(LED)

Optional Accessory



Single side cylinder or both side cylinder, other sizes are available too: 80/90/100/110/120mm.



Single side cylinde




Double side cylinder



Single side cylinder with Thumb


Optional accessory

The Door Loop is used for protection of extension wiring from damages for security reasons.




Adjustable Latch bolt


Please adjust the position of the latch bolt according to the door opening direction.



Installation Schematic





EL-600C(LED)



EL-630C(LED)

Installation steps



Wiring Diagram

