



Standalone Outdoor waterproof controller


support EM+HID+MF card

Feature:

- Waterproof, conforms to IP66
- One relay, 600 users
- Card type: 125KHz EM card, 125KHz HID card, and 13.56Mhz Mifare Card
- PIN length: 4~6 digits
- Wiegand 26~37 bits input & output
- Can be used as Wiegand reader with LED & Buzzer output
- Pulse mode, Toggle mode
- 2 devices can be interlocked for 2 doors
- 12~28V AC/ DC



3 working modes



C

Detail specification:

User Capacity	600
Common Users	598
Panic Users	2
Operating Voltage	12~28V AC/DC
Idle Current	< 65mA
Active Current	< 100MA
Proximity Card Reader	HID & EM & Mifare
Radio Technology	125KHz & 13.56Mhz
Read Range	2~6 cm
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand input, Wiegand output
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
Wiegand Interface	Wiegand 26~37bits
Wiegand Input	26~37bits
Wiegand Output	26~37bits
PIN Output	4 bits, 8 bits(ASCII), 10 digits Virtual Number
Environment	Meets IP66
Operating Temperature	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Operating Humidity	0%RH ~ 98%RH
Physical	Zinc-Alloy Enclosure
Surface Finish	Powder Coat
Dimensions	L150xW51xH23mm
Unit Weight	500g
Shipping Weight	600g