



SR07E/M (84.5x44x16.8mm)

-E: 125KHz Proximity Card Reader



SR05E/M (77.5x42.8x16.5mm)

-M: 13.56MHz Mifare Card Reader



SR12E/M with Keypad (86x86x16.3mm)

## Product Introduction

RFID Wiegand reader as client reader or connect to Access Control Panel via wiegand-out interface.

## Features:

- 125KHz Proximity /13.56MHz Mifare Card Reader.
- Read Range: Up to 10CM(125KHz)/5CM(13.56MHz).
- 26/34bit Wiegand (default).
- Easy to install on Metal Door Frame or Mullion.
- External LED Control and Buzzer Control.
- Indoor / Outdoor Operation.
- Waterproof IP65
- Reverse Polarity Protection

## Technical Specification

- Read Range: -E Up to 10CM; -M Up to 5CM
- Reading Time (Card): ≤300ms
- Power / Current: DC 6-14V / Max.70mA
- Input Port: 2ea (External LED Control, External Buzzer Control)
- Output Format: -E: 26bit Wiegand (default); -M: 36bit Wiegand (default)
- LED Indicator: 2 Color LED Indicators(Red and Green)
- Beeper: Yes
- Operating Temperature: -10° to +70°C
- Operating Humidity: 10% to 90% relative humidity non-condensing
- Material: ABS+PC with texture 12V DC 3A
- Index of Protection: IP65