



**Model:** SR01EM Dual Reader

Support Both 125KHz Proximity & 13.56MHz Mifare Card

**Description:** RFID Wiegand reader as client reader or connect to Access Control Panel via wiegand-out interface

## Features:

- ▶ 125KHz Proximity & 13.56MHz Mifare Card Reader.
- ▶ Read Range: Up to 10CM(125KHz) & 5CM(13.56MHz).
- ▶ 26/34bit Wiegand (default).
- ▶ Easy to install on Metal Door Frame or Mullion.
- ▶ External LED Control and Buzzer Control.
- ▶ Indoor / Outdoor Operation.
- ▶ Waterproof IP65
- ▶ Reverse Polarity Protection

## Technical Specification:

- ▶ Read Range: 5-10CM
- ▶ Reading Time (Card):  $\leq 300$ ms
- ▶ Power / Current: DC 6-14V / Max.70mA
- ▶ Input Port: 2ea (External LED Control, External Buzzer Control)
- ▶ Output Format: 26/34bit Wiegand (default)
- ▶ LED Indicator: 2 Color LED Indicators(Red and Green)
- ▶ Beeper: Yes
- ▶ Operating Temperature:  $-10^{\circ}$  to  $+70^{\circ}$ C
- ▶ Operating Humidity: 10% to 90% relative humidity non-condensing
- ▶ Material: ABS+PC with texture 12V DC 3A
- ▶ Index of Protection: IP65